




**FITTING INSTRUCTIONS FOR ECC0077 LHS ENGINE CASE COVER
KAWASAKI Z1000 2010-**



In this kit there should be:
1 x Engine Case Cover (ECC0077)
3 x M6x40mm long button head bolt

PLEASE READ THESE INSTRUCTIONS FULLY BEFORE STARTING


- Please make sure the engine is cold before proceeding with the fitting of the R&G cover.
- Remove the two lower fairing bolts arrowed on the right hand side in the above picture to allow fitting of this product.
- Remove the three engine case bolts arrowed in picture. Hold the cover loosely over the case to help identify the correct ones. **DO NOT REMOVE ALL OF THE CASE BOLTS.**
- Offer up the R&G cover to the engine and carefully fit it over the engine casing. Ensure that the R&G bolt holes are lined up with the holes in the engine casing, and then push on as far as it will go.
- With a 4mm Allen key tighten the bolts equally so that they pull the cover into place. **DO NOT FULLY TIGHTEN.**
- Finally use a torque wrench set at 10 nm (7 Lb ft) to fully tighten.
- Replace the two lower fairing bolts.
- It is suggested that you check the tightness of the mounting bolts on a regular basis i.e. when cleaning or once a month.
- NOTE for the cleaning of this product you should only use a soft polishing cloth and a mild general cleaning agent.
- **AVOID HARMFUL CHEMICALS IF IN DOUBT DO NOT USE AS THEY COULD ALTER THE STRENGTH OF THE COVER.**
- R&G will accept no liability if the above procedure and torque settings are not followed.

R&G RACING

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



**INSTRUCTIONS DE MONTAGE
ECC0077 LHS PROTECTION CARTER GAUCHE
KAWASAKI Z1000 2010**



Le kit contient:

1 x Protection carter (ECC0077)
3 x M6x40mm Longs boulons à tête ronde

Lire les instructions avant de procéder au montage

- Veiller à ce que le moteur de la moto soit froid.
- Enlever les deux boulons de carénage du bas comme fléché sur le coté droit sur la photo du dessus pour poursuivre l'installation.
- Enlever les 3 boulons de fixation du carter moteur (photo). Tenir la protection autour du carter pour aider à identifier les bons trous.
- **Ne pas enlever tous les boulons du carter moteur.**
- Mettre en place la protection R&G au moteur en prenant soin de bien le positionner autour du carter moteur.
- S'assurer que les trous de la protection R&G soient bien alignés avec ceux du carter, puis pousser jusqu'à la limite.
- Avec une clé Allen de 4mm, serrer les boulons de façon égale pour qu'ils mettent automatiquement la protection en place.
- **NE PAS SERRER COMPLETEMENT.**

R&G RACING

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



- Pour finir, utilise une clé dynamométrique réglée à 10nm (7 Lb ft) pour serrer définitivement.
- Remettre les 2 boulons de carénage du bas.
- Note importante:
 - vérifier le serrage des vis au moins une fois par mois.
 - Le nettoyage de la protection, doit se faire à l'aide d'un produit nettoyant non agressif et à l'aide d'un chiffon doux.
- L'UTILISATION D'AGENT NETTOYANT TROP PUISSANT PEUT ALTERER LA FINITION DE VOTRE PROTECTION R&G.
- Aucune garantie ne sera acceptée par R&G en cas de mauvais couple de serrage et en cas d'utilisation de nettoyeurs trop agressifs.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G RACING

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com