



FITTING INSTRUCTIONS FOR FP0014BK FORK PROTECTORS YAMAHA R6 '03-'04

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

- Take bobbin with the hex neck
Position the protector with the hex neck in front of the left side of the front wheel spindle (left as you sit on the bike)
- Place soft cloth in front of protector
- Tap the protector into place
- Remove the original bolt from the right hand side of the spindle, and replace it with the one supplied (tighten to recommended torque setting, not available from R&G)
- Take the second bobbin and slide it over the head of the bolt
- Push the long bar right through the whole assembly, until it comes out on the other side
- Place one washer on each end of the bar
- Place nyloc nuts on each end of the bar and tighten them – do not overtighten them. Just tighten them until they lock up – as they are nyloc nuts they will hold tight

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.