




FITTING INSTRUCTIONS FOR FP0074BK FORK PROTECTORS YAMAHA DT125R AND DT125X



Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

Right-hand side (as you sit on bike)

- Remove the rubber grommet from front wheel spindle if fitted.
- Place spindle bar through spindle.
- Place smaller spacer with spigot over spindle so the spacer spigot fits into spindle bore and rests against the spindle nut as shown above left.
- Place either bobbin over spindle bar against spacer just fitted as shown above left.
- Place washer and nut from kit on right-hand of spindle bar, leaving nut loose.

Left-hand side (as you sit on bike)

- Place bigger remaining spacer over spindle bar.
- Place remaining bobbin over spindle bar against spacer just fitted as shown above left.
- Place washer and nut on spindle bar and into bobbin counter-bore.
- Using two sockets tighten the assembly ensuring both nuts are engaging into, and biting into, the nyloc nuts - Do not overtighten – the nyloc nuts will hold it tight.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com



than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



FRANCE
INSTRUCTIONS DE MONTAGE DE LA PROTECTION DE FOURCHE
FP0074BK
YAMAHA DT125R et DT125X

Merci de noter que les pièces assemblées dans l'emballage ne sont pas nécessairement dans le sens du montage à réaliser sur la moto.

Droit

- Enlever la pièce en caoutchouc fixée sur l'axe de roue avant.
- Placer l'entretoise la plus petite dans l'axe de roue, la partie la plus large sera place vers l'extérieur de l'axe de la moto.

Gauche

- Placer l'entretoise la plus grande dans l'axe de roue.

- Placer la barre R&G à travers les entretoises R&G.
- Placer les tampons.
- Glisser une rondelle de chaque côté et placer ensuite un écrou autobloquant de chaque côté.
- A l'aide de deux clés, serrez les deux écrous simultanément.
- Ne pas serrer trop fortement, en effet les écrous autobloquants vont garder le montage en place.