



**FITTING INSTRUCTIONS FOR LP0069BK LICENCE PLATE HOLDER  
YAMAHA YZF-125R 2008>**



- NOTE YOU WILL NEED TO GLUE THE LIGHT SHROUD TO THE LED LICENCE PLATE LIGHT BEFORE FITTING USING SUPER GLUE.
- Remove seat.
- Remove rear cowling to allow access to the wiring plugs.
- Remove OEM licence plate holder.
- Remove OEM indicators from licence plate holder if they are to be re-used.
- Remove the rubber grommet from the OEM unit and fit to the R&G licence plate holder.
- If fitting after-market mini indicators try R&G mini-indicators ( product code RG370 ).
- If not already fitted, fit new No plate light to R&G licence plate holder.
- Fit OEM or after-market indicators to R&G licence plate holder.
- Offer up new licence plate holder to original mounting points (feeding wires through as original) and using OEM bolts secure and tighten R&G licence plate holder.
- Connect indicators and No plate light (**suggest cutting connector from OEM unit and splicing to R&G unit using connectors supplied**)
- Refit rear cowling.
- Refit seat.
- Depending on local laws, attach enclosed red reflective tape in an appropriate location.
- Test the indicators and licence plate illuminator before riding.



#### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



## Notice de montage

**LP0069BK SUPPORT DE PLAQUE YAMAHA 125 YZF-R 2008>**



### Conseil de montage:

**MERCI DE LIRE LA NOTICE AVANT DE COMMENCER LE MONTAGE DE LA PIECE.**

- Enlevez la selle.
- Enlevez les carénages latéraux de la selle. Ceci afin d'avoir un accès aux fiches électrique.
- Démontez le support de plaque d'origine.
- Démontez les clignotants d'origine du support d'origine, si vous les réutilisez.
- Enlevez la pièce en caoutchouc se trouvant sur le support d'origine, et placée la ensuite sur le support R&G.
- Remontez les clignotants de votre choix sur le support R&G.
- Montez ensuite l'éclairage de plaque sur le support R&G.
- Positionnez le support sur la moto, glissez les câbles à travers le support R&G et à travers le passage de câbles d'origine.
- Fixez le support à l'aide des vis d'origine.
- Reconnectez les clignotants et l'éclairage de plaque sur le faisceau électrique d'origine. (nous vous suggérons de couper les connecteurs d'éclairage d'origine et de les remplacer par les connecteurs livrés dans le kit de montage).
- Testez le bon fonctionnement des clignotants et de l'éclairage de plaque.
- Remettez les carénages de selle.
- Remontez la selle sur la moto

**Egalement disponible pour cette moto :**

**Tampons moteur**



**Diabolos**



**Embout de Guidon**



R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)



R&G Racing  
Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX  
Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)