

# Fitting Instructions for OCG0019BK Oil Cooler Guard BMW R NINE T '14-



In This Kit There Should Be
1x Oil Cooler Guard (OCG0019)
2x 4mm Cable ties
2x 100mm Length of self-adhesive foam







Picture 2







Picture 3 Picture 4

- To fit the oil cooler guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the oil cooler guard frame, so that they sit between the oil cooler guard and the radiator.
- Remove the two bolts that secure the original oil cooler guard in place at the top behind the steering damper, as shown in picture 1.
- Offer the R&G oil cooler guard (OCG0019BK) into place on the oil cooler radiator and re-fit the two original bolts through the oil cooler guard and into the oil cooler mount, as shown in pictures 2 & 3.
- Fit 1x cable tie through the slot on each lower corner and loop it through the radiator matrix before tightening, as shown in picture 4.
- Ensure all bolts are tightened evenly and the oil cooler guard is mounted securely.

ISSUE 1 12/03/2014 (AR)

#### CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



# INSTRUCTIONS DE MONTAGE POUR OCG0019BK Grille de protection BMW R NINE T '14-



### Le kit doit contenir :

1x Grille de protection (OCG0019)
2x 4mm colliers de serrage
2x 100mm Longueur de mousse autocollante



Photo 1



Photo 2







Photo 3 Photo 4

- Couper la mousse en bandeaux de 10mm puis collez ces bandeaux au bas du support de protection radiateur, de façon à ce que ces bandeaux se situent entre la protection radiateur et le radiateur.
- Enlever les 2 boulons qui fixent la grille de protection refroidisseur d'huile en place au dessus derrière l'amortisseur de direction (photo 1).
- Mettre la grille refroidisseur d'huile en place (OCG0019BK) sur le radiateur refroidisseur d'huile puis remettre les 2 boulons d'origine à travers la grille de protection refroidisseur d'huile et dans le support refroidisseur d'huile (photos 2 & 3).
- Passer un collier de serrage à travers la fente sur chaque coin inférieur puis encerclez à travers la matrice de radiateur, avant de serrer (photo 4).
- Assurez-vous que tous les boulons soient serrés de façon égale et que la protection refroidisseur d'huile soit correctement montée.

ISSUE 1 12/03/2014 (AR)

#### CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms in has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

#### **R&G Racing**



## Montageanleitung für den OCG0019BK Ölkühlerschutz BMW R NINE T – AB MODELL 2014



<u>Dieser Kit enthält:</u>
1x Kühlerschutz (OCG0019)
2 x 4mm Kabelbinder
2x 100mm selbstklebender Schaumstoffstreifen



ABBILDUNG 1



ABBILDUNG 2







**ABBILDUNG 3** 

**ABBILDUNG 4** 

- Um den Ölkühlerschutz am Motorrad zu montieren, schneiden Sie zuerst die mitgelieferten Schaumstoffstreifen in 10 mm breite Streifen und kleben Sie diese auf der Rückseite des Ölkühlerschutzrahmens, so dass sie zwischen dem Ölkühlerschutz und dem Ölkühler angebracht sind.
- Entfernen Sie die zwei Schrauben, die den Originalölkühler oben hinter dem Lenkungsdämpfer befestigen siehe Abbildung 1.
- Den R&G Ölkühlerschutz (OCG0019BK) an den Ölkühler ansetzten und die zwei Originalschrauben durch den Ölkühlerschutz und die Ölkühlerhalterung einführen und befestigen siehe Abbildungen 2 & 3.
- Die Kabelbinder durch die Öffnung an den unteren Ecken einfädeln und um das Gitter wickeln, danach befestigen Sie sie siehe Abbildung 4).
- Überprüfen Sie, dass alle Schrauben sicher montiert und gleichmäßig festgezogen sind.

AUSGABE 1 12/03/2014 (AR)

#### CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms in has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

### R&G Racing