



Fitting Instructions for RAD0164 BK/OR Radiator Guard
KTM 390 DUKE 2013



In This Kit There Should Be
1x Radiator Guard (RAD0164BK/OR)
4 x Cable/Zip Tie
2x 100mm Lengths of self adhesive Foam

- To fit the radiator guard to the bike, cut the foam strip provided into 10mm wide pieces and stick them to the back of the radiator guard frame, so that they sit between the radiator guard and the radiator.

Fitting Instructions

- Undo and remove the 2 retaining nuts on the upper mounting points above the Radiator
(Arrow #1 on pic)
 - Leave the spring washers in place on the protruding studs
- Undo and remove the 2 retaining nuts & spring washers on the lower mounting points below the radiator (Arrow #2 on pic)
 - Fit the radiator guard into place locating on the 4 protruding studs
 - Tighten all 4 nuts to secure the radiator guard
- The spring washers will be underneath the radiator guard on the upper mounting points, and on top of the radiator guard on the lower mounting points



ISSUE 1 20/11/2013 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.

Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



Instructions de montage



Couper la mousse en bandeaux de 10mm et collez-les au bas de la protection radiateur pour que les bandeaux soient entre la protection et le radiateur.

Instructions de montage

- Desserrer et enlever les 2 écrous de fixation sur les points de fixation supérieurs au dessus du radiateur (Fléché #1 sur la photo.).
- Laissez les rondelles à ressort en place sur les goujons en saillie.
- Desserrer et enlever les 2 écrous de fixation & les rondelles à ressort sur les points de fixation inférieurs au dessous du radiateur (Fléché #2 sur la photo).
- Mettre la grille radiateur en place sur les 4 goujons en saillie.
- Serrer les 4 écrous pour fixer la grille radiateur.
- Les rondelles à ressort seront sous la protection de la grille R&G sur les points de fixation supérieurs, et au-dessus de la grille de protection radiateur sur les points de fixation inférieurs.





Montageanleitung für den RAD0164BK Kühlerschutz
KTM 390 DUKE 2013



Dieser Kit beinhaltet:
1x Kühlerschutz (RAD0164BK)
4 x Kabelbinder
2x 100mm selbstklebende Schaumstoffstreifen

- Um den Kühlerschutz am Motorrad zu montieren, schneiden Sie zuerst die mitgelieferten Schaumstoff-Streifen in 10 mm breiten Streifen und kleben Sie diese auf der Rückseite des Kühlerschutzrahmens, so dass sie zwischen dem Kühlerschutz und dem Kühler angebracht sind.

Montageanleitung

- Lösen und entfernen Sie die 2 Befestigungsschrauben an den oberen Montagepunkten über dem Kühler (Pfeile #1 auf dem Bild).

R&G Racing
Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



- Lassen Sie die Federringe auf den vorstehenden Bolzen.
- Lösen und entfernen Sie die 2 Befestigungsschrauben an den unteren Montagepunkten unter dem Kühler (Pfeile #2 auf dem Bild)
 - Montieren Sie den Kühlerschutz an den 4 vorstehenden Bolzen.
 - Drehen Sie alle 4 Mutter fest, um den Kühlerschutz zu befestigen.
- An den oberen Montagepunkten sind die Federringe unter dem Kühlerschutz und an den unteren Montagepunkten sind sie auf dem Kühlerschutz.



AUSGABE 1 20/11/2013 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.

Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G Racing
Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com