Page: 1 TP0029



# FITTING INSTRUCTIONS FOR TP0029 FOOTBOARD SLIDERS SUPER SOCO CPX 2020-



### THIS KIT CONTAINS THE ITEMS PICTURED AND LABELLED OVER PAGE.

SOME PARTS MAY BE SHOWN FOR CLARITY OF INSTRUCTIONS ONLY.

DO NOT PROCEED UNTIL YOU ARE SURE ALL PARTS ARE PRESENT.

### PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING.

# IF IN ANY DOUBT WHEN FITTING OUR PRODUCTS, CONSULT ONE OF OUR DEALERS OR HAVE FITTED BY A QUALIFIED TECHNICIAN.

PLEASE NOTE THAT THE WAY THE KIT IS PACKED DOES NOT NECESSARILY REPRESENT THE WAY OF MOUNTING TO THE BIKE.

IN THE EVENT OF RUBBER WASHERS BEING USED TO HOLD COMPONENTS ONTO BOLTS,

THESE RUBBER WASHERS CAN BE THROWN AWAY.

# DIGITAL COPIES OF THESE INSTRUCTIONS ARE AVAILABLE FROM:

WWW.RG-RACING.COM



# **TOOLS REQUIRED**

- Set of metric Hex keys Set of metric sockets and wrench.

# **GENERAL TORQUE SETTINGS**

M4 BOLT = 8Nm

M5 BOLT = 12Nm

M6 BOLT = 15Nm

M8 BOLT = 20Nm

M10 BOLT = 40Nm

M12 BOLT = 40Nm

# **LEGEND**

ITEM No.	DESCRIPTION	QTY
ITEM 1	SLIDER (SL0007)	2
ITEM 2	M6 x 1.00 x 25mm LONG COUNTERSUNK BOLTS	4
ITEM 3	M5 x 1.00 x 12.00mm LONG COUNTER SUNK BOLT	6
ITEM 4	SPACER (S0848) 13mm LONG	4
ITEM 5	MOUNTING PLATE LHS (SMW0179)	1
ITEM 6	MOUNTING PLATE RHS (SMW0180)	1
ITEM 7	RUBBER INSERT (RG0033)	2



Page: 3












IMAGE 3: IMAGE 4:

### **FITTING INSTRUCTIONS**

- Firstly, remove the 4x OE bolts from the footboards (**Image 1**) and place the 4x spacers (**Item 4**) the position shown in **Image 2**.
- Assemble the R&G foot-board sliders as shown in Image 3 by holding the sliders in position on the mounting plate and inserting the smaller M5 bolts (Item 3) through the slider and thread into the mounting plate. Then place the rubber insert into position on the mounting plate.
- Place the assembly onto the foot-board and align the countersunk holes of the mounting plate with the spacers on the foot-board and carefully thread in the supplied 2x M6 bolts (**Item 2**) and tighten down to their required torque setting.
- Repeat this process for the other side of the foot-board.

### Please Note:

Thread lock is recommended on all bolts to prevent them from loosening due to vibrations or being worked loose from repetitive use.

ISSUE 1 - 09/04/2021 (TB)

Page: 4 TP0029



#### CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



# NOTICE DE MONTAGE POUR TP0029 SLIDERS DE MARCHEPIEDS SUPER SOCO CPX 2020-



### CE KIT CONTIENT LES ARTICLES ILLUSTRES ET ETIQUETES SUR LA PAGE.

CERTAINES PARTIES PEUVENT ETRE PRESENTES UNIQUEMENT POUR LA CLARTE DES INSTRUCTIONS.

NE PAS PROCEDER AU MONTAGE TANT QUE VOUS N'ETES PAS SUR QUE TOUTES LES PIECES SOIENT PRESENTES.

VEUILLEZ LIRE TOUTES LES INSTRUCTIONS AVANT DE CONTINUER.

# EN CAS DE DOUTE LORS DU MONTAGE DE NOS PRODUITS, CONSULTEZ UN DE NOS REVENDEURS OU FAITES APPEL A UN TECHNICIEN QUALIFIÉ.

VEUILLEZ NOTER QUE LA FAÇON DONT LE KIT EST EMBALLE NE REPRESENTE PAS NECESSAIREMENT LA MANIERE DE LE MONTER SUR LA MOTO.

SI DES RONDELLES EN CAOUTCHOUC SONT UTILISEES POUR MAINTENIR LES COMPOSANTS SUR LES BOULONS, ELLES PEUVENT ETRE JETEES.

### **NOTICE DISPONIBLE AU TELECHARGEMENT SUR:**

WWW.RG-RACING.COM



# **OUTILS REQUIS**

• Clés hexagonales Clé à cliquet + douilles.

# **VALEURS DE SERRAGE**

M4 BOULON = 8Nm

M5 BOULON = 12Nm

M6 BOULON = 15Nm

M8 BOULON = 20Nm

M10 BOULON = 40Nm

M12 BOULON = 40Nm

# LÉGENDE

ARTICLE	DESCRIPTION	QTÉ
No.		
ARTICLE 1	SLIDER (SL0007)	2
ARTICLE 2	M6 x 1.00 x 25mm BOULONS	4
ARTICLE 3	M5 x 1.00 x 12.00mm BOULON	6
ARTICLE 4	ENTRETOISE (S0848) 13mm DE LONG	4
ARTICLE 5	PLAQUE DE MONTAGE CÔTÉ GAUCHE (SMW0179)	1
ARTICLE 6	PLAQUE DE MONTAGE CÔTÉ DROIT (SMW0180)	1
ARTICLE 7	INSERT EN CAOUTCHOUC (RG0033)	2



Page: 7












IMAGE 3: IMAGE 4:

## **NOTICE DE MONTAGE :**

- Tout d'abord, retirez les 4x boulons d'origine des marchepieds (Image 1) et placez les 4x entretoises (Article 4) à la position indiquée sur l'image 2.
- Assemblez les sliders R&G de marchepied, comme indiqué sur l'image 3 en maintenant les sliders en position sur la plaque de montage et en insérant les plus petits boulons M5 (article 3) à travers le slider et en les vissant dans la plaque de montage. Placez ensuite l'insert en caoutchouc en place sur la plaque de montage.
- Placez l'ensemble sur le marchepied et alignez les trous fraisés de la plaque de montage avec les entretoises du marchepied et vissez soigneusement les 2x boulons M6 fournis (article 2) et serrez au couple de serrage requis.
- Répétez ce processus pour l'autre côté du marchepied.
   Veuillez noter :

Page: 8 TP0029



Un blocage de filetage est recommandé sur tous les boulons pour éviter qu'ils ne se desserrent en raison des vibrations ou qu'ils ne soient desserrés suite à une utilisation répétée.

ISSUE 1 - 09/04/2021 (TB)

#### CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

### **R&G RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.